



# Ethernet to 1-Port RS-232 Serial Server

**Part:** 4101 | **Model:** SeaLINK.232

The 4101 Ethernet to serial server is the easiest way to connect RS-232 serial devices to your Ethernet network. Each RS-232 port implements all modem control signals for maximum compatibility with a wide range of peripherals. SeaLINK® products use industry-standard RFC 2217 TCP/IP protocol for maximizing compatibility with the widest range of applications and devices.

Sealevel's SeaLINK software drivers and utilities make installation and operation easy using Microsoft Windows operating systems. After software installation, the 4101's serial ports appear as virtual COM ports to the host machine. Standard serial operating calls are transparently redirected to the 4101, guaranteeing compatibility with legacy serial devices and enabling backward compatibility with existing software. Serial tunneling is also supported, allowing two native serial devices to communicate over a network. Alternatively, raw data socket mode is supported, eliminating the need for a driver.

To simplify installation and configuration, a printed copy of the SeaLINK QuickStart Guide is included with all Ethernet serial server orders.

## Features & Specifications

### Ethernet to 1-Port RS-232 Serial Server

**Part:** 4101 | **Model:** SeaLINK.232

#### Features

- Ethernet 10/100BaseT (autosense)
- Appears as a virtual COM port to host machine
- Data rates to 230.4K bps
- Supports custom baud rates and 9-bit protocol
- Single DB9M connector with full modem control signals implemented
- Hot-swappable
- Built-in watchdog/reset circuit automatically recovers the converter from unexpected error-states
- Includes 120V AC adapter that outputs 5VDC @ 1A (Item# TR107)
- Includes 7' Ethernet patch cable (Item# CA246) and 7' Ethernet crossover cable (Item# CA251)
- Sealevel SeaLINK software supports Microsoft Windows and Linux operating systems

#### Specifications

<b>Family</b>	SeaLINK
<b>Dimensions</b>	5.0 (L) x 4.2 (W) x 1.1 (H)
<b>Electrical Interface</b>	RS-232
<b>Humidity Range</b>	10 – 90% Relative Humidity, Non-Condensing
<b>Host Interface(s)</b>	Ethernet
<b>Max Data Distance</b>	50 feet
<b>Max Data Rate</b>	230.4K bps
<b>Operating Temperature</b>	0°C to 70°C (32°F to 158°F)
<b># of Ports</b>	1
<b>Power Requirement</b>	+5V @ 500mA
<b>Serial Connector(s)</b>	DB9M
<b>Storage Temperature</b>	-50°C to 105°C (-58°F to 221°F)