



# RS-485 Modbus RTU Interface to 16 Isolated Inputs / 8 Form C Relay Outputs

**Part:** 420M | **Model:** Seal/O-420M

Control and monitor 16 optically isolated inputs and 8 Form C (SPDT) relay outputs with the Seal/O-420M. Inputs can range from 5-30VDC, while the Form C relays provide switch closures up to 60VDC @ 2A. Inputs and outputs are grouped into four-bit segments that each share a common for easy wiring via removable 3.5mm terminal blocks. The Seal/O-420M is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-420M using industry-standard Modbus RTU protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

## Features & Specifications

### RS-485 Modbus RTU Interface to 16 Isolated Inputs / 8 Form C Relay Outputs

Part: 420M | Model: Seal/O-420M

#### Features

- RS-485 Modbus RTU interface
- 16 optically isolated inputs
- 8 SPDT Form C relays
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- DIN rail or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

#### Specifications

<b>Family</b>	Seal/O
<b>Contact Bounce Time</b>	7ms max.
<b>Contact Current</b>	2A max.
<b>Contact Operate Time</b>	2ms max.
<b>Contact Release Time</b>	1ms max..
<b>Contact Voltage</b>	60VDC max.
<b>Digital I/O</b>	Form C Relay Outputs, Isolated Inputs
<b>Dimensions</b>	7.5 (L) x 5.1 (W) x 1.3 (H)
<b>Extended Temperature</b>	Call for Options
<b>Humidity Range</b>	10 – 90% Relative Humidity, Non-Condensing
<b>Input Isolation</b>	300V
<b>Input Range</b>	5-30 VDC
<b>Host Interface(s)</b>	RS-485
<b>Number of Inputs/Outputs</b>	16 Inputs / 8 Outputs
<b>Operating Temperature</b>	0°C to 70°C (32°F to 158°F)
<b># of Ports</b>	16/8
<b>Power Requirement</b>	9-30 VDC @ 2.0W
<b>RoHS Compliant</b>	Yes
<b>Storage Temperature</b>	-50°C to 105°C (-58°F to 221°F)