



32 Reed Relay Output Seal/O Expansion Module

Part: 440N | **Model:** Seal/O-440N

The Seal/O-440N adds 32 Reed relay outputs to your Seal/O network. Reed relays offer long life performance and fast response time. Each relay can switch up to 60VDC @ 500mA. Compatible with all Seal/O base units (Ethernet, USB, RS-485, RS-232), the Seal/O-440N connects easily using an RS-485 input. Cabling is accomplished via the units RJ45 connector or removable screw terminals. RS-485 line conditioning allows easy installation of termination and pull-up/pull-down resistors.

All Seal/O N-series expansion modules ship with an expansion and strap kit that includes four metal straps, four #4-40 screws, and a 5" RJ45 RS-485 interconnect cable. The metal straps allow you to connect multiple Seal/O modules together in a stack. The interconnect cable can be used to connect Seal/O modules together via the RJ45 pass-through connectors, providing an easy method to cascade RS-485 signals and power from one module to the next. Alternatively, use inexpensive CAT5 cabling to pass data signals between Seal/O modules to create a distributed network.

Features & Specifications

32 Reed Relay Output Seal/O Expansion Module

Part: 440N | Model: Seal/O-440N

Features

- Quick connection to Seal/O devices using RJ45 connector or removable screw terminals
- 2 SPST Reed relays
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- DIN rail mount or table mount Includes expansion and strap kit (item# KT122)

Specifications

Family	Seal/O
Contact Bounce Time	0.5ms max.
Contact Current	500mA max.
Contact Operate Time	0.5ms max.
Contact Release Time	0.2ms max.
Contact Voltage	60VDC max.
Digital I/O	Reed Relay Outputs
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	Expansion
Number of Inputs/Outputs	32 Outputs
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	32
Power Requirement	9-30 VDC @ 2.5W
RoHS Compliant	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)