



# Wi-Fi 802.11b/g Modbus TCP to 96 Channel TTL Digital Interface Kit - 462W + (2) CA237 Cables

**Part:** 462W-KT | **Model:** Seal/O-462W with Cables

The Seal/O-462W wireless to digital I/O interface module provides 96 channels of buffered drive digital I/O. The interface module addresses the 96 channels of I/O as 12 eight-bit ports, each programmable as input or output. Using the included shielded cables (Item# CA237), connect up to four industry-standard relay racks for PC based control and automation of equipment including sensors, switches, security control systems, and other industrial automation systems.

The Seal/O-462W makes the I/O available via dual DB-78 female connectors. The Seal/O-462W is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-462W over Wi-Fi (802.11b and 802.11g) networks using industry-standard Modbus TCP protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. Security features include WEP and the latest WPA-TKIP and WPA2-AES encryption standards.

The Sealevel Modbus Connect app for iOS allows you to access the registers, coils and discrete I/O of your Sealevel Modbus devices and is available on the App Store. Use the app to remotely access I/O in the field or for testing and troubleshooting during application development.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

## Features & Specifications

### Wi-Fi 802.11b/g Modbus TCP to 96 Channel TTL Digital Interface Kit - 462W + (2) CA237 Cables

**Part:** 462W-KT | **Model:** Seal/O-462W with Cables

#### Features

- Complies with 802.11g and 802.11b (2.4GHz) networking standards
- Wireless security supports WEP, WPA-TKIP, and WPA2-AES encryption standards
- 96 channels of buffered TTL I/O via two DB-78 female connectors
- Each 8-bit port individually configurable as input or output
- Includes two 6' cables, part number CA237, each with a DB-78 Male connector to dual 50-pin ribbon connectors
- Easily connects to industry-standard solid-state relay racks with 50-pin connectors
- Status indicator LEDs for Communication, Fault, and Power
- Input power via terminal block or modular connector
- DIN rail or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

#### Specifications

<b>Family</b>	Seal/O
<b>Digital I/O</b>	TTL I/O
<b>Dimensions</b>	7.5 (L) x 5.1 (W) x 1.3 (H)
<b>Extended Temperature</b>	Call for Options
<b>Frequency Range</b>	2.412 – 2.484 GHz
<b>Humidity Range</b>	10 – 90% Relative Humidity, Non-Condensing
<b>Host Interface(s)</b>	Wi-Fi (802.11bgn)
<b>Kit</b>	Yes
<b>Number of Inputs/Outputs</b>	96 TTL
<b>Operating Temperature</b>	0°C to 70°C (32°F to 158°F)
<b>Output Power</b>	14dBm +1.5/-1.0 dBm
<b>Output Specification</b>	Sink up to 64mA, Source up to 32mA
<b># of Ports</b>	96
<b>Power Requirement</b>	9-30 VDC @ 2.0W
<b>Storage Temperature</b>	-50°C to 105°C (-58°F to 221°F)
<b>Wireless Channels</b>	11 (US)13 (Europe, Japan)
<b>Wireless Range</b>	328' (Indoors)
<b>Wireless Data Rates</b>	54Mbps Max.1Mbps Min.
<b>Wireless Standards</b>	802.11b802.11g802.11i