

Features & Specifications

USB to 16 Isolated Inputs / 16 Open-Collector Outputs

Part: 530U | Model: Seal/O-530U

Features

- 16 optically isolated inputs
- 16 open collector outputs
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- Sealevel's SeaLATCH locking USB port provides secure connection with SeaLATCH USB cables via metal thumbscrews
- Optional DIN rail or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems
- Includes 6' USB type A to SeaLATCH USB type B device cable (Item# CA356)

Specifications

Family	Seal/O
Digital I/O	Isolated Inputs, Open-Collector Outputs
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Input Isolation	2500VAC RMS, 3500VDC
Input Range	5-30 VDC
Input Impedance	6.2 K Ohms (in series)
Host Interface(s)	USB
Number of Inputs/Outputs	16 Inputs / 16 Outputs
Operating Temperature	-25°C to 85°C (-13°F to 185°F)
Output Dissipation	Max. 1000mA (single), Max. 2000mA (port)
Output Isolation	2500VAC RMS, 3500VDC
Output Power	DC 60W max.
Output Type	Open-Collector
Output Voltage	Max. 60VDC
# of Ports	16/16
Power Requirement	9-30 VDC @ 1.7W
RoHS Compliant	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)