

PCI Express 16 Isolated Input Digital Interface (10-30V)

Part: 8006He | Model: ISO-16.PCle

Optimized for sensing up to 24V inputs, the 8006He PCI Express digital I/O interface provides 16 optically isolated inputs for connection to devices including sensors, switches, pushbuttons, and other user inputs. The inputs can sense both AC and DC voltage while providing optical isolation, which eliminates spikes and surges present in industrial environments. The board is PCI Express X1 compliant and is compatible with any PCI Express slot.

The inputs on the 8006He are rated for 10-30V. For 3-13V inputs, order the 8006e.

Sealevel SealO Classic software drivers and utilities make installation and operation of the 8006He easy using Microsoft Windows operating systems.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.



Features & Specifications

PCI Express 16 Isolated Input Digital Interface (10-30V)

Part: 8006He | Model: ISO-16.PCle

Features

- · Compliant with RoHS and WEEE directives
- · PCI Express X1 compliant
- 16 optically isolated AC or DC inputs
- Socketed dip resistor allows user configurable input range up to +24V
- Power (+5V and +12V) and ground provided on DB78 board connector
- Includes 72" cable with DB78 Male connector to DB37 Female connector (Item# CA489)
- SealO Classic software supports Microsoft Windows operating systems
- · Software support for Linux available

Specifications

DB-78F
(1) DB-37F
Isolated Inputs
Call for Options
10 – 90% Relative Humidity, Non- Condensing
3 – 50mA
300V
10-30 VDC
PCI Express
16 Inputs
0°C to 70°C (32°F to 158°F)
Standard Height
16
Yes
-50°C to 105°C (-58°F to 221°F)

