



USB to 16 Isolated Inputs / 8 Form C Relay Outputs Digital Interface Adapter

Part: 8222 | **Model:** SeaDAC PLC-24

Control and monitor 16 optically isolated inputs and 8 Form C (SPDT) relay outputs via any USB connection with the 8222. Inputs can range from 5-30VDC, while the Form C relays switch up to 60VDC @ 2A. Inputs and outputs are grouped in four-bit segments that each share a common for easy wiring via removable 3.5mm terminal blocks.

SeaDAC modules are housed in a rugged, attractive plastic enclosure and include a highly-retentive USB Type B connector to prevent accidental disconnection. The 8222 is USB bus-powered, so no external power supply is needed. Standard operating temperature range of SeaDAC modules is 0°C to 70°C and extended temperature range (-40°C to 85°C) is optional.

The SeaMAX software suite supports the SeaDAC family and is designed to work with third-party applications via the SeaMAX API software libraries, or use any Modbus RTU compliant device. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

Features & Specifications

USB to 16 Isolated Inputs / 8 Form C Relay Outputs Digital Interface Adapter

Part: 8222 | **Model:** SeaDAC PLC-24

Features

- 16 optically isolated inputs
- 8 SPDT Form C relays
- Removable screw terminals simplify field wiring
- High-retention USB Type B connector prevents accidental disconnection of USB cable
- Powered by USB connection
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems
- Housed in rugged, attractive plastic enclosure
- 72-inch USB A to B cable included (Item# CA179)

Specifications

Family	SeaDAC
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Contact Current	2A max.
Contact Operate Time	2ms max.
Contact Release Time	1ms max.
Contact Voltage	60VDC max.
Digital I/O	Form C Relay Outputs, Isolated Inputs
Dimensions	9.2 (L) x 5.3 (W) x 1.7 (H)
Extended Temperature	Call for Options
Contact Bounce Time	7ms max.
Input Range	5-30 VDC
Input Isolation	300V
Host Interface(s)	USB
Modbus	Modbus RTU
Number of Inputs/Outputs	16 Inputs 8 Outputs
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	16/8
Power Requirement	+5V @ 500mA
Serial Connector(s)	DB9M
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Specification	1.1 Compliant, 2.0 Compatible