



Rugged SuperSpeed 7-Port USB 3.1 Hub

Part: HUB7SSBA | **Model:** Rugged SuperSpeed 7-Port USB 3.1 Hub

The HUB7SSBA features a rugged, industrial-grade, metal housing, robust ESD protections, USB 3.1 compliance and backward compatibility with legacy USB data rates. The HUB7SSBA is designed to meet the advanced requirements for connecting multiple USB peripherals in extreme environments while achieving SuperSpeed operation.

Redefining Rugged

The Rugged SuperSpeed USB 3.1 Hub checks every box for industrial use:

- USB 3.1 compliant, providing up to 5 Gb/s data rate to the host
- -40°C to +85° operating temperature
- Individual port power management
- 15kV ESD protections on USB 3.0 data lines
- 8kV ESD protections on USB 2.0 data lines
- Up to 1500mA available on all ports simultaneously
- Comprehensive input power protections (reverse polarity, voltage surge, overcurrent, under-voltage, over-voltage)
- Includes 2-meter USB 3.0 type A to USB 3.0 type B device cable (Item #CA783)
- Wide operating voltage range (9V-30V)
- Multiple Transaction Translator (MTT) design prevents data rate bottlenecks when legacy USB devices are attached
- Powered by your 9-30 VDC source or select an optional power supply (Item #TR152)
- Optional DIN rail mounting kit (Item #DR106)

Charging Downstream Ports

The HUB7SSBA ships with port 7 configured as a Charging Downstream Port (CDP) capable of supplying up to 2.4A of current to a connected device. The remaining six CDPs supply up to 1500 mA to each connected device. All CDPs are USB Battery Charging Specification BCv1.2 compliant, ideal for charging batteries or powering high-current USB peripherals. The Multiple Transaction Translator (MTT) design prevents speed limitations, enabling multiple high bandwidth devices to operate at SuperSpeed.

Each downstream port has a Bi-Color Status LED that indicates two types of connections:

- USB 3.1/3.0 connection to the host will cause the LED to illuminate GREEN
- USB 2.0/1.1/1.0 connection to the host will cause the LED to illuminate YELLOW

Features & Specifications

Rugged SuperSpeed 7-Port USB 3.1 Hub

Part: HUB7SSBA | **Model:** Rugged SuperSpeed 7-Port USB 3.1 Hub

SeaLATCH High-Retention, Locking Connectors

The HUB7SSBA integrates Sealevel's SeaLATCH locking USB 3.0 ports, which are fully compatible with standard USB cables. Optional SeaLATCH USB cables provide a secure connection to the device and prevents accidental cable disconnection. The hub's seven SeaLATCH USB 3.0 type A connectors can secure downstream USB peripherals to the hub in the same way. The ports are compatible with both SeaLATCH USB 3.0 and SeaLATCH USB 2.0 cables.

Features

- USB 3.1 hub provides seven Charging Downstream USB Ports (CDPs)
- One Charging Downstream Port (CDP) supplies up to 2.4A to a connected device (Port 7)
- Six Charging Downstream Ports (CDPs) supply up to 1500mA to each connected device
- CDPs are battery charging specification BCv1.2 compliant
- Supports SuperSpeed (5Gb/s), high-speed (480Mb/s), full-speed (12Mb/s) and low-speed (1.5Mb/s) operation
- ESD protection
- ±8kV on Each USB 2.0 Data Line (D+, D-)
- ±15kV on Each USB 3.0 Data Line (SSTX+, SSTX-, SSRX+, SSRX-)
- Fully Supported in Microsoft Windows 8/10 and other USB-aware operating systems (compatible with all operating systems that support USB 1.1/2.0/3.0)
- Optional wall-mount AC power supply accessory outputs 24VDC @ 2.71A (Item #152) and mates via the HUB7SSBA's included locking DC terminal block/connector
- Includes 2-meter USB 3.0 type A to USB 3.0 type B device cable (Item #CA783)
- Sealevel's SeaLATCH locking USB 3.0 ports provide secure connection with SeaLATCH USB 3.0 cables via metal thumbscrews
- Reverse polarity input voltage protection down to -40VDC with respect to GND
- Overvoltage Protection against input voltage surges up to 80VDC with respect to GND
- Overcurrent Protection against short circuits and excessive load currents

Easy Installation & Use

Fully Supported in Microsoft Windows 8/10, and backward compatible with Microsoft Windows XP/7, and other USB-aware operating systems. The hub requires no separate drivers and is easy to install.

Industrial Design & Operation

The HUB7SSBA features a rugged, metal enclosure and can be mounted utilizing the optional DIN Rail Mounting Kit (Item # DR106). Standard operating temperature range is -40°C to 85°C.

Specifications

Communications Chip	USB Hub (USB5807C)
Dimensions	7.5in (L) x 5.125in (W) x 1.75in (H)
Humidity Range	10 – 95% Relative Humidity, Non-Condensing
Max Data Distance (When Using USB 3.0 functionality)	3 Meters with Standard Passive USB 3.0 Cables, 18 Meters with an Active USB 3.0 Cable
Max Data Distance (When Using USB 2.0 Functionality)	5 Meters with Standard Passive USB 2.0 Cables, 30 Meters with an Active USB 2.0 Cable
Max Data Rate	5 Gb/s (SuperSpeed)
Operating Temperature	-40°C to 85°C (-40°F to 185°F)
# of Ports	7
Power Requirement(s)	9-30VDC via TR152
RoHS Compliant	Yes
USB Specification	USB 3.1 Gen 1, SuperSpeed (USB 3.0) Compliant; 2.0, 1.1, 1.0 Compatible