



PCI 2-Port RS-232 Serial Interface

Part: 7202c | **Model:** COMM+232.PCI: PCI 2 Port RS-232 (7202c)

The 7202c PCI serial interface provides two RS-232 serial ports capable of data rates to 1.0 Mbps. Each RS-232 port implements all modem control signals for maximum compatibility with a wide range of peripherals. The 7202c utilizes two, independent, enhanced 16550 compatible UARTs that provide 256-byte Tx/Rx FIFOs.

Sealevel's SeaCOM software makes installation and operation easy using Microsoft Windows and Linux operating systems.

Features & Specifications

PCI 2-Port RS-232 Serial Interface

Part: 7202c | **Model:** COMM+232.PCI: PCI 2 Port RS-232 (7202c)

Features

- Enhanced 16550 compatible UARTs with 256-byte FIFOs
- Data rates to 1.0 Mbps
- All modern control signals implemented
- Two DB-9M connectors

Specifications

Communications Chip	XR17V352 (16550 Compatible UART)
Electrical Interface	RS-232
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	PCI
Max Data Distance	50 feet
Max Data Rate	1.0 Mbps
Operating Temperature	-40°C to 85°C (-40°F to 185°F)
PC Bracket	Standard Height
# of Ports	2
Serial Connector(s)	DB9M
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
UART Series	XR17V352 Series